

# A Review Study- Base Shear Reduction by Using Optimum Size of Beam in Top Floors in Multistoried Building at Different Levels

Shubham Patel<sup>1</sup>, Ankit Pal<sup>2</sup>

<sup>1</sup>M Tech Scholar, Department of Civil Engineering, Oriental University, Indore, India

<sup>2</sup>Assistant Professor, Department of Civil Engineering, Oriental University, Indore, India

**Abstract**— India is the country where infrastructure is going very fast and also our country fastest emergent economy in the world and infrastructure plays a extremely very important responsibility in it. The Construction of high-rise structure in India is growing day by day. Consequently fresh thoughts and venture are wanted to make the structure secure, financial and durable. The base shear reduction by use of most favorable Size of Beam in Top Floors in Multistoried Building at different level is the one of the . It reduces the dimension of beam at the top floors of the structure to decrease its self-weight.

**Keywords**— Base Shear, Beam Size, Base Shear Reduction, High Rise Structures.

## I. INTRODUCTION

The humankind is emergent more rapidly and the requirement of the world is that the fresh thoughts and technology in area of construction. The multistory building and high rise structure are the today's humankind requirement. To create them secure, safe, long-lasting and suitable it is very desirable to include fresh thoughts of construction in it. The reduction of base shear under seismic loading is the new method. In this method the beam size of the building top floors are reduced which helps to reduce the base shear of the building under seismic loading. It also makes the building economic and reduces the dead load of the building.

### Column

Column is the vertical member which helps to transmit load to one end to another. It is prepared with reinforced cement concrete (RCC). Its major benefit is that it refuse to accept compressive load.

### Beam

Beam is the Horizontal member which helps to transmit load to slab to column. It is prepared with reinforced cement concrete (RCC). Its major benefit is that it accept tension load.

### Shear Wall

It is a member of structure which used to resist lateral forces i.e. wind force, seismic force. In further words,

Shear walls are members to resist the horizontal forces on structures. Shear wall provides strength to the structure.




Fig. 1: 3D View of model with various size of beam size at top floor

### Multistorey building

When the building has numerous storey's it is known as multistory building. And it contains perpendicular flow in the form of lifts, stairs and ramps. The multistory buildings are the want of today's contemporary world because it carries additional loads and offer extra strength

than solo storey buildings. It reduces the ground use and consequently makes overall expenditure lowest.

### Base Shear

Base shear is the sliding force that is generated at the bottom of the building especially due to earthquake forces. Base shear of a building is directly proportional to its weight.




Fig. 2: 3D View of model with various size of beam size at different level of top floor

Above model shows the variation of beam size in the structure. As per the figure shows the high rise structure with shear wall. It is also consider as model for reduction of base shear due to various range of beam size.

## II. LITERATURE REVIEW

### Wensheng LU et. al.

The paper briefs about the tests of some scaled high-rise multi-tower structure models on the trembling table. By considering the effect of flexible transfer floor in a new analytic model is shown. The test result considers the theoretical dynamic behavior comparison. The combination floors between towers at top levels, and the stiffness of foundation role to structural dynamic behavior is also described in this paper. Many suggestions and theoretical guidelines are also accomplished.

### Priyanka Soni et. al.

Research paper study shows Shear walls are structural systems which offer stability to structures from sideways loads similar to wind, seismic loads. Author study about the stability. These structural systems are built by RCC, plywood and timber un-reinforced masonry, reinforced masonry at which these systems are sub separated into

coupled shear walls, shear wall frames, shear panels and staggered walls. Paper examine the shear wall situation also. The current study shows in the paper that attention of studying and analysis of a variety of examine works concerned in development of shear walls and their performance towards tangential loads. As shear walls resist main portion of tangential loads in the lesser portion of the structure and the frame supports the lateral loads in the higher portions of building which is suitable for soft storey high rise building, building which are similar in nature constructed in India, We have also find out the physically calculation of all cases is more time consumable as see in reference paper both physically and software based are calculated but we have completed and obtained results approximately. So used of software is reasonably priced.

### Tiwari Darshita et. al.

As per Researcher Concrete is the the majority beyond doubt and crucial matter being utilize in building structure all through the humankind Umpteen variety of concretes were study in numerous laboratories and brought to the ground to go with the exact wants. though, normal fine aggregates (i.e. river sand) are so far and/or will be better to any further matter in manufacture concrete but their accessibility is incessantly being exhausted suitable to the deliberate overexploitation all through the earth due to fast urbanization and manufacture of other facilities. therefore, part substitute of fine aggregate by the other well-matched matter like sintered fly ash, flattened rock dust, quarry dust, glass powder, reused concrete dust and others are being investigate from the precedent twenty years, in vision of conserve the ecological balance. In this direction, an test examination of strong point and toughness was undertake to use "Spent Fire Bricks" (SFB) (i.e. devastate matter from foundry bed and walls; and lining of chimney which is adopt in many industries) and "Glass Powder" for part alternate of fine aggregate in concrete.

### N. Anand et. al.

As per paper Self compact concrete (SCC) is a latest age group of concrete that consolidates with no any outside attempt. Due to its compensation over the conventional concrete, the use of of SCC increase gradually. thoughtful of the behavior of SCC is vital in the design of building subjected to prominent heat. A learning was conceded out to recognize the behavior of S.C.C. beams of a variety of grades uncovered to prominent temperature in flexural loading. The beams were uncovered to a temperature of 900\_C. The warm sample were refrigerated moreover by water or air. The investigate exertion was conceded out for diverse grades of concrete. It is establish from the outcome that the failure of strength

of SCC beams of superior grades was more than that of the lesser grade SCC beams. It was also established that the decrease in compressive, tensile and flexural strength of the sample depend on kind of warm up and cooling circumstances

### C. Marthong et. al.

The Researcher write The consumption of fly ash in RCC or concrete as part substitute of cement is accepting huge significance nowadays, mostly on report of the development in the long-standing toughness of concrete joint with environmental profit. Three grades of OPC specifically: 33, 43 and 53 as classify by BIS are normally utilize in manufacture business. This essay reports a relative learning on effects of concrete property when OPC of changeable grades were partly replace by fly ash. The main changeable investigate in this learning is deviation of fly ash amount of 10% , 20% , 30% and 40% . The compressive strength, durability and shrinkage of concrete were mostly premeditated. Test outcome show that, enclosure of fly ash usually improve the concrete property up to convinced percent of substitute in all grades of OPC.

### Aasif Khan et. al.

As author write By reviewing and analyzing above literatures I found that no one have discussed and work on Base Shear Reduction by Using Optimum Size of column in Top Floors of multistorey building. Reducing the column size on the top floor of the building is the new way of reducing cost as well as dead load of the structure. And there are more efforts and work is needed on this top. The base shear reduction by using Optimum Size of column in Top Floors in Multistoried Building under seismic loading is the one of them. It reduces the size of column at the top levels of the building to reduce its self-weight

### Aasif Khan et. al.

At the present days the structure are ready with lots of current traditions like tall structure etc and there necessity is satisfied by fresh modernization and latest thoughts. A multiplicity of innovators bounded by them used to build the structure with their own alternative and also the insist of market. The parameter of assessment of consequence such as displacement and storey drift are obtained in fundamentals of the any multistoried structure situated in earthquake Zone-III, earthquake effects are acting on the building under 7 diverse best sizes of column for decrease of base shear. For base shear decrease using the best dimension of column columns with same concrete grade in multistoried building under seismic loading, to study the decrease of base shear and inspect with the alliance of E-Tabs design software. As per proportional outcomes in all

parameters model F and Model G is very efficient in all Models respectively.




Fig. 3: Maximum Bending Moment in Column

From all the results, we consider the maximum bending moment in column the outcome in all parameters model F and Model G is very efficient in respectively as well as for all model cases.

### Mahendra Kumawat et. al.

The researcher state that this study analyses the different parameters of design software model with different grades like stresses displacements base shear etc in longitudinal and transverse direction. After this, the most efficient grading will be analyzed after all parameters. There are total 5 grades of structure multistoried building at medium soil condition under seismic forces for earthquake zone III exist. In this investigate, the parameter of evaluation of result such as displacement and storey drift are obtained in requisites of the twin tower multistoried structure located in earthquake Zone-III, earthquake effects are performing on the construction under 5 different Shapes and scrutinize with the assistant of Staad pro design software. The overall result shows shape Z and U is very efficient cases for twins tower.

### Abrar Ahmad et. al.

This paper summarizes that it is really important to use analytical methods before construction of multistory buildings in seismic and non-seismic areas. By reviewing all the Papers we can easily understand the importance of analytical methods. We can easily calculate the effect of seismic loading by using the software's like staad pro and E-tabs before construction of multistory buildings. Calculation and modeling is the main purpose of the conclusion The Analysis is carried out for seismic zone III. The structure model are analyzed and compared with different porch location for the seismic zone III as per IS 1893-2016 for response spectrum analysis. The assessment of results is carried out for Displacement, Storey Shear, and Base Shear etc. The results are obtained and

represented in the forms of graphs and tables for the seismic zone. location 1 is very efficient cases for porch in building.

### III. CONCLUSION

By reviewing and analyzing various research processes it is seem that in field of base shear reduction by using Optimum Size of Beam in Top Floors in Multistoried Building at different level has many possibilities. It is study that durability depend on the shear reduction. It is required to observe that the structure with various possibilities of Reduction of base shear. By comparing various model in seismic zone and it is observed that it is having high resisting tendency to seismic zone.

### REFERENCES

- [1] Wensheng LU and Xilin LU (2000), Seismic Model Test and Analysis of Multi-Tower High-Rise Buildings, the 12th International Conference on Tall Buildings, paper 0281, pp. 01-08.
- [2] Suyash Malviya, Sagar Jamle, (2019), "Response of Multistorey Building with Rooftop Telecommunication Tower in Different Positions: An Approach to Efficient Case", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 4, pp. 3783-3790.
- [3] Priyanka soni, Purushottam Lal Tamrakar, Vikky Kumhar (2016), Structural Analysis of Multistory Building of Different shear Walls Location and Heights, International Journal of Engineering Trends and Technology (IJETT), Volume 32, ISSN 2231-5381 pp. 50-57.
- [4] Yash Joshi, Sagar Jamle, (2019), "Effect of Curtailed Shear Wall on Dynamic Analysis of RC Building", International Journal of Management, Technology And Engineering, (ISSN: 2249-7455(O)), vol. 9, no. 7, pp. 223-230.
- [5] Sagar Jamle, Dr. M.P. Verma, Vinay Dhakad, (2017), "Flat Slab Shear Wall Interaction for Multistoried Building under Seismic Forces", International Journal of Software & Hardware Research in Engineering (IJSHRE), ISSN: 2347-4890 Vol.-05, Issue-3, pp. 14-31.
- [6] Tiwari Darshita, Patel Anoop (2012), Study of Strength and Workability of Different Grades of Concrete by Partial Replacement of Fine Aggregate by Crushed Brick and Recycled Glass Powder, International Journal of Science and Research (IJSR), Volume 3 Issue 6,, ISSN (Online): 2319-7064pp. 141-145.
- [7] Romesh Malviya, Sagar Jamle, (2020), "Increasing Stability of Multistoried Building using Different Grades of Concrete in Column Member Sets at Different Locations", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 208-213. <https://doi.org/10.14741/ijcet/v.10.2.3>
- [8] N. Anand, G. Prince Arulraj (2014), Effect of Grade of Concrete on the Performance of Self-Compacting Concrete Beams Subjected to Elevated Temperatures, Springer Science+Business Media New York. Manufactured in The United States DOI: 10.1007/s10694-013-0345-6, ISSN 1269-1284 pp. 1269-1270.
- [9] Mohit Kumar Prajapati, Sagar Jamle, (2020), "Strength irregularities in multistoried building using base isolation and damper in high Seismic zone: A theoretical Review", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 235-238. <https://dx.doi.org/10.22161/ijaers.73.37>
- [10] Gagan Yadav, Sagar Jamle, (2020), "Opening Effect of Core Type Shear Wall Used in Multistoried Structures: A Technical Approach in Structural Engineering", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 344-351. <https://dx.doi.org/10.22161/ijaers.73.50>
- [11] C. Marthong, T.P. Agrawal(2012) Effect of Fly Ash Additive on Concrete Properties International Journal of Engineering Research and Applications Vol. 2, Issue4, ISSN: 2248-9622, pp.1986-1991
- [12] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "A Review on Stability Improvement with Wall Belt Supported Dual Structural System Using Different Grades of Concrete", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 3, pp. 293-296. <https://dx.doi.org/10.22161/ijaers.73.43>
- [13] Gagan Yadav, Sagar Jamle, (2020), "Use of Shear Wall with Opening in Multistoried Building: A Factual Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 243-246. <https://doi.org/10.14741/ijcet/v.10.2.9>
- [14] Khan A. , Pal A. (2020). A Review on Base Shear Reduction by using same Grade of Concrete by Optimizing Size of Column Member International Journal of Current Engineering and Technology, Vol.10, No.2 , P-ISSN 2347-5161 E-ISSN 2277- 4106 pp 269-271.
- [15] Sagar Jamle and Roshan Patel, (2020), "Analysis and Design of Box Culvert- A Manual Approach in Structural Engineering", LAP LAMBERT Academic Publishing, Mauritius, ISBN: 978-620-0-78760-6.
- [16] Gaurav Pandey, Sagar Jamle, (2018), "Optimum Location of Floating Column in Multistorey Building with Seismic Loading", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 5, no. 10, pp. 971-976.
- [17] Aasif Khan. , Ankit Pal. (2020) Reduction of Base Shear Using Different Size of Columns with Same Concrete Grade in Multistoried Building under Seismic Loading Journal of Xi'an University of Architecture & Technology, Volume XII, Issue IV, 2020 ISSN No. : 1006-7930 p p 5060-5069
- [18] Sachin Sironiya, Sagar Jamle, M. P. Verma, (2017), "Experimental Investigation On Fly Ash & Glass Powder As Partial Replacement Of Cement For M-25 Grade Concrete", IJSART - Volume 3 Issue 5, ISSN- 2395-1052, pp. 322-324.

- [19] Surendra Chaurasiya, Sagar Jamle, (2018), "Determination of Efficient Twin Tower High Rise Building Subjected to Seismic Loading", International Journal of Current Engineering and Technology, INPRESSCO, E-ISSN 2277 – 4106, P-ISSN 2347 – 5161, Vol. 8, No. 5, pp. 1200 – 1203, DOI: <https://doi.org/10.14741/ijcet/v.8.5.1>.
- [20] Archit Dangi, Sagar Jamle, (2018), "Determination of Seismic parameters of R.C.C. Building Using Shear Core Outrigger, Wall Belt and Truss Belt Systems". International Journal of Advanced Engineering Research and Science (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 5, no. 9, pp.305-309 AI Publications, <https://dx.doi.org/10.22161/ijaers.5.9.36>
- [21] Mohd. Arif Lahori, Sagar Jamle, (2018), "Investigation of Seismic Parameters of R.C. Building on Sloping Ground", International Journal of Advanced Engineering Research and Science, (ISSN: 2349-6495(P), 2456-1908(O)), vol. 5, no. 8, pp.285-290 AI Publications, <https://dx.doi.org/10.22161/ijaers.5.8.35>
- [22] Suyash Malviya, Sagar Jamle, (2019) , "Determination of Optimum Location of Rooftop Telecommunication Tower over Multistory Building under Seismic Loading", International Journal of Advanced Engineering Research and Science (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 6, no. 2, 2019, pp. 65-73, AI Publications, <https://dx.doi.org/10.22161/ijaers.6.2.9>
- [23] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistory Building", International Journal for Research in Engineering Application & Management (ISSN : 2454-9150), vol. 4, no. 10, pp. 596-603, doi: 10.18231/2454-9150.2018.1372.
- [24] Neeraj Patel, Sagar Jamle, (2019), "Use of Shear Wall Belt at Optimum Height to Increase Lateral Load Handling Capacity in Multistory Building: A Review", International Journal of Advanced Engineering Research and Science (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 6, no. 4, pp. 310-314, AI Publications, <https://dx.doi.org/10.22161/ijaers.6.4.36>
- [25] Taha A. Ansari, Sagar Jamle, (2019), "Performance Based Analysis of RC Buildings with Underground Storey Considering Soil Structure Interaction", International Journal of Advanced Engineering Research and Science (ISSN: 2349-6495(P) | 2456-1908(O)), vol. 6, no. 6, pp. 767-771, AI Publications, <https://dx.doi.org/10.22161/ijaers.6.6.89>
- [26] Sagar Jamle and Shirish Kumar Kanungo, (2020), "Determination of Stable Underground Storage Reservoir System- Recent Advancements in Structural Engineering Volume 1", LAP LAMBERT Academic Publishing, Mauritius, ISBN: 978-620-2-51435-4.
- [27] Prakash Mandiwal, Sagar Jamle, (2019), "Tensile Strength & Durability Study on Self-Curing Concrete as a Partial Replacement of Cement by PEG-400", International Journal for Research in Engineering Application & Management (ISSN : 2454-9150), vol. 4, no. 10, pp. 244-248, doi: 10.18231/2454-9150.2018.1314
- [28] Surendra Chaurasiya, Sagar Jamle, (2019), "Twin Tower High Rise Building Subjected To Seismic Loading: A Review". International Journal of Advanced Engineering Research and Science (ISSN : 2349-6495(P) | 2456-1908(O)), vol. 6, no. 4, pp. 324-328, AI Publications, <https://dx.doi.org/10.22161/ijaers.6.4.38>
- [29] Archit Dangi, Sagar Jamle, (2019), Stability Enhancement of Optimum Outriggers and Belt Truss Structural System", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 2, pp. 772-780.
- [30] Mohd. Arif Lahori, Sagar Jamle, (2019), "Response of Multistory Building Located on 20 degree and 30 degree Sloping Ground under Seismic Loading", International Research Journal of Engineering and Technology, (ISSN: 2395-0072(P), 2395-0056(O)), vol. 6, no. 1, pp. 1063-1069.
- [31] Mariyam and Sagar Jamle (2020), "Wind Analysis of Flat Slab Multistoried Building Construction: "Recent Advancements in Structural Engineering": Volume II, LAP LAMBERT Academic Publishing, Mauritius.
- [32] Durgesh Kumar Upadhyay, Sagar Jamle, (2020), "Stability Enhancement in Wall Belt Supported Dual Structural System using Different Grades of Concrete", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 237-242. <https://doi.org/10.14741/ijcet/v.10.2.8>
- [33] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by using Optimum Size of Beams with same Grade of Concrete: An Informative Review", International Journal of Current Engineering and Technology, (ISSN: 2277-4106 (O), 2347-5161(P)), vol. 10, no. 2, pp. 259-262. <https://doi.org/10.14741/ijcet/v.10.2.12>
- [34] Manoj Patidar, Sagar Jamle, (2020), "Optimization of Stability of Multistoried Structure by Changing Grades of Concrete in Shear Wall Member", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 2479-2497. <https://doi.org/10.37896/JXAT12.04/979>
- [35] Sagar Jamle, Dr. M.P. Verma, Vinay Dhakad, (2017), "Flat Slab Shear Wall Interaction for Multistoried Building Analysis When Structure Length is greater than width under seismic Forces", International Journal of Software & Hardware Research in Engineering (IJSHRE), ISSN: 2347-4890 Vol.-05, Issue-3, pp. 32-53.
- [36] Pankaj Kumar Dhakad, Sagar Jamle, (2020), "Base Shear Reduction by Using Optimum Size of Beams in Top Floors with Different Grades in Multistoried Building at Different Levels", International Journal of Advanced Engineering Research and Science, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 293-296. <https://dx.doi.org/10.22161/ijaers.74.20>
- [37] Sagar Jamle, Nirmal Delmiya, Rahul Singh, (2020), "Efficient Use of UPV Meter: A Non Destructive Test of Concrete by Fragmentation Analysis", Journal of Xi'an University of Architecture & Technology, ISSN: 1006-7930, vol. 12, no. 4, pp. 3385-3394. <https://doi.org/10.37896/JXAT12.04/1078>

- [38] Manoj Patidar, Sagar Jamle, (2020), "Use of different Grades of Concrete in Shear Wall: A Comprehensive Review", *International Journal of Advanced Engineering Research and Science*, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 4, pp. 355-359.  
<https://dx.doi.org/10.22161/ijaers.74.44>
- [39] Mohammad Bilal Rasheed, Sagar Jamle, (2020), "Conceptual Approach on Effect of Various Concrete Grade in Outrigger and Wall Belt Supported System: A Perceptual Review", *International Journal of Advanced Engineering Research and Science*, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 100-104.  
<https://dx.doi.org/10.22161/ijaers.75.14>
- [40] Shahdab Khan, Sagar Jamle, (2020), "Use of Shear Wall Member at Corners to Enhance the Stability Using Different Grades: An Immense Review", *International Journal of Advanced Engineering Research and Science*, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 396-400.  
<https://dx.doi.org/10.22161/ijaers.75.47>
- [41] Ankush Nagar, Sagar Jamle, (2020), "Base Shear Reduction Techniques: A Review", *International Journal of Advanced Engineering Research and Science*, (ISSN: 2456-1908 (O), 2349-6495(P)), vol. 7, no. 5, pp. 466-471.  
<https://dx.doi.org/10.22161/ijaers.75.57>
- [42] Kumawat, M., Pal, A. and Choudhary, M. (2020). "Determination of efficient Shape of twin tower subjected to Seismic Loading". *International Journal of Advanced Engineering Research and Science*, 7(2), pp.95-99
- [43] Abrar Ahmad, Ankit Pal, Mayank Choudhary(2020)," Review Analysis On Determine The Best Location Of Porch In Multistory Building With And Without Seismic Loading" *International Journal of Advanced Engineering Research and Science (IJAERS) Vol-7, Issue-1 ISSN: 2349-6495(P) | 2456-1908(O) pp182-184*