https://dx.doi.org/10.22161/ijaers/nctet.2017.ece.10 ISSN: 2349-6495(P) | 2456-1908(O)

An Optimal Energy Monitoring System Using Internet of Things (IOT)

G.BHANU PRAKASH[1] P.R.SIDDA REDDY[2]

[1]PG scholar, Department Of ECE (Embedded Systems), S.V College Of Engineering,Tirupati, A.P,India

[2]Assistant Professor, Department Of ECE, S.V College Of Engineering,Tirupati , A.P,India

Email: [1]geepalembhanuprakash@gmail.com, [2]siddu.polimera@gmail.com

ABSTRACT—Many potential packages were developed inside the fields of evaluation and automation. On this paper, a platform becomes designed to attach sensor records with customers daily existence. As an utility of it, Any manipulate - a domestic home equipment tracking and controlling machine changed into carried out. although home equipment are getting extra wise each day. no longer handiest are manufacturers promoting new clever appliances; there are also many clever telephone orientated faraway controller products. but modern merchandise constantly have platform compatibility troubles, additionally, user interaction in such structures is becoming increasingly complex. This work proposes an approach to beautify vintage appliances and the controlling revel in through an IoT based domestic appliance Controlling device. with present day monitoring sensors, the home equipment can be managed surroundings circumstance cause. The modern-day sensor information are processed with the aid of unmarried-board computer and brought to web applications via Wi-Fi Ethernet connection. The outcomes of implementation and experimentation has shown the proposed gadget and platform can offer greater IoT application possibilities daily life solution.

Keywords:* *Raspberry Pi, Current sensor, Wi-Fi, power supply, relay.

1. INTRODUCTION:

Figuring out and decreasing strength waste is hard whilst there may be restricted statistics approximately which devices are using how a great deal energy. With the proliferation of smaller power using gadgets in residential and industrial buildings (i.e., plug hundreds), the number of character gadgets and their mixture electricity use is increasing. In homes and industrial buildings, plug masses represent 30% of the whole energy use moreover, the quantity of strength used by plug hundreds is developing faster than every other load class in each sectors .A big fraction of these hundreds are electronics, and digital gadgets present a unique and awesome opportunity to leverage the internet of factors (IoT) for know-how and decreasing strength use. The problem is particularly acute for the massive range of small, electricity-the use of gadgets which might be found in each residential and industrial homes. most of these products use a switching ac to dc strength supply to function digital and different inner additives. A "communicating strength supply" (CPS), to allow the communication of power and manipulate statistics between the tool and a building control system or different vital entities may be advanced.

Existing System

Within the present gadget, the technique carried out is the use of a wireless radio transmission to switch the facts to the server, which makes the method complex and also an outside server must be deployed in order to get right of entry to and control the home equipment.

Proposed System

Proposed device includes an enhance Linux primarily based device, will design and advanced our personal web server to acquire the intake statistics and show at the webpage for tracking, also will control the appliances turn on/off from net and based totally on intake threshold values. such as

https://dx.doi.org/10.22161/ijaers/nctet.2017.ece.10 ISSN: 2349-6495(P) | 2456-1908(O)

storing all of the log records of the consumption in a Pen drive will be finished.

2. BLOCK DIAGRAM



Figure 1: Block diagram of the project

Block diagram Description

Lowering the power use of plug loads becomes an increasing number of important, because the quantity of electronic devices grows and the stop uses in homes become more green. but, nowadays solutions for saving electricity are primarily based on either long-time period power policy methods or transitional technology that don't perform as purchasers assume or preference. lowering the electricity use of plug. for you to enforce this a raspberry board with ARM eleven processor has been used in conjunction with AC hundreds i.e. bulb and motor. This gadgets are connected to gpio pins of the board. Ethernet router is attached to the board to permit the wireless data switch of the values and controlling the burden on/off. A USB pen drive is used to shop the log facts of the device with electricity intake in a textual content record periodically.

3. SOFTWARE

3.1. QT

The software is used to design and developed is QT writer that is used to make green GUI application. Qt author is a good instance of an utility that mixes distinctive user interface technology. In reality, it uses all of the 3 special procedures defined underneath. Qt writer makes use of the conventional Qt Widgets along with menus and dialogs as a basis of the user interface, Qt brief among others for the welcome display, and Qt WebKit for providing the Qt reference documentation. Qt author includes a task manager that uses a move platform mission record layout (.seasoned). A challenge record can contain statistics which includes what files are blanketed into the venture, custom build steps and settings for jogging the applications. Qt creator includes a code editor and integrates Qt fashion designer for designing and constructing graphical person interfaces (GUIs) from Qt widgets. The code editor kcan parse code in C++ and QML languages... it is feasible to compose and personalize the widgets or dialogs and take a look at the ones the usage of one-of-a-kind styles and resolutions without delay in the editor. Widgets and forms created with Qt clothier are incorporated with programmed code, the usage of the Qt indicators and slots mechanism.

3.2. Raspbian Operating System

Raspbian is a free running machine based on Debian optimized for the Raspberry Pi hardware. An running system is the set of simple applications and utilities that make your Raspberry Pi run. however, Raspbian offers greater than a pure OS: it comes with over 35,000 applications, pre-compiled software bundled in a pleasant layout for smooth set up for your Raspberry Pi..The initial construct of over 35,000 Raspbian packages, optimized for first-class performance at the Raspberry Pi, became finished in June of 2012. however, Raspbian is still under lively development with an emphasis on improving the steadiness and overall performance of as many Debian programs as possible. The Raspberry Pi broadly speaking uses Linux kernel-primarily based operating structures Raspbian

International Journal of Advanced Engineering Research and Science (IJAERS) Special Issue-4
https://dx.doi.org/10.22161/ijaers/nctet.2017.ece.10 ISSN: 2349-6495(P) | 2456-1908(O)

(advocated) – Maintained independently of the foundation; based on ARM tough-float (armhf)-Debian 7 'Wheezy' architecture port, that become designed for a newer ARMv7 processor (or one with Jazelle RCT/ThumbEE, VFPv3 and NEON SIMD extensions built-in) whose binaries could no longer work on the Raspberry Pi, but Raspbian is compiled for the ARMv6 coaching set of the Raspberry Pi making it work but run extra slowly. It offers some available deb software applications, pre-compiled software bundles. A minimal length of two GB SD card is required, however a 8 GB SD card or above is recommended. there is a Pi shop for replacing programs. The Raspbian Server version is a stripped model with different software programs bundled in comparison to the usual computer laptop oriented Raspbian.

4. HARDWARE

4.1. Raspberry Pi (ARM 11)

The Raspberry Pi is a credit-card sized computer that plugs into your television and keyboard. it's far a capable for little tasks, and for most of the matters that your laptop does, like spreadsheets, phrase-processing and games. It also plays high-definition videos. We need to see it being used by youngsters all around the world to learn the way computer systems paintings, how to control the digital international round them and, the way to application. The original Raspberry Pi is primarily based at the Broadcom BCM2835 system on a chip (SoC), which incorporates, Video center IV GPU, RAM of 512 MB. The gadget has comfortable digital (SD) socket for boot media and chronic garage. A SoC includes the hardware, described above, and the software controlling the microcontroller, microprocessor or DSP cores, peripherals and interfaces. The design waft for Soc aims to increase this hardware and software in parallel.

Figure 2: Raspberry –pi Board

4.2. Current Sensor

A current sensor is a tool that detects electric powered contemporary (AC or DC) in a twine, and generates a sign proportional to it. The generated sign might be analog voltage or modern-day or maybe digital output. it is able to be then utilized to show the measured cutting-edge in an ammeter or may be stored for similarly analysis in a data acquisition system or may be utilized for control reason. There are a huge style of sensors, and every sensor is suitable for a particular modern-day range and environmental circumstance. nobody sensor is premier for all packages.

International Journal of Advanced Engineering Research and Science (IJAERS) Special Issue-4
https://dx.doi.org/10.22161/ijaers/nctet.2017.ece.10 ISSN: 2349-6495(P) | 2456-1908(O)

Figure 3: Current sensor

C) Relays:

A relay is an electrically controllable switch extensively used in industrial controls, cars and appliances. The relay allows the isolation of separate sections of a system with different voltage sources i.e., a small quantity of voltage/cutting-edge on one aspect can deal with a big quantity of voltage/cutting-edge on the other aspect however there may be no chance that those voltages mix up.

Operation:

Whilst current flows via the coil, a magnetic subject is created around the coil i.e., the coil is energized. This reasons the armature to be interested in the coil. The armature's contact acts like a switch and closes or opens the circuit. whilst the coil isn't energized, a spring pulls the armature to its normal state of open or closed. There are all sorts of relays for all types of packages

5. RESULTS

Figure 5 displays the web page in which the user can view the load current and voltage and can also turn on and turn off the loads.



Figure 4: Hardware assembly of the project

Figure 5: Display over monitor

6. CONCLUSION:

We presented an Internet-connected system of CPSs that enables improved energy awareness of devices and users. We believe that CPS technology is the future of energy monitoring for plug loads, and that all energy-using devices will one day be aware of their identity and share energy information over IP networks. The CPS concept we have shown here demonstrates that this concept is valid at reasonable price points even for quite low-cost devices. Energy awareness enables new sets of interactive energy-saving behaviours where devices control their power state to meet user needs while minimizing energy use. Unlike existing technologies, CPS devices are integrated into the product to provide native controls and automatically include product identity information. The low cost, reduced configuration burden, and tight coupling with the powered product make CPSs an tremendous application of IoT concepts.

7. FUTURE SCOPE

In the near future the Internet and wireless technologies will connect different sources of information such as sensors, mobile phones and cars in an ever tighter manner. The number of devices which connect to the Internet is – seemingly exponentially – increasing. These billions of components produce consume and process information in different environments such as logistic applications, factories and airports as well as in the work

International Journal of Advanced Engineering Research and Science (IJAERS) *Special Issue-4*
https://dx.doi.org/10.22161/ijaers/nctet.2017.ece.10 *ISSN: 2349-6495(P) | 2456-1908(O)*

and everyday lives of people. The society need new, scalable, compatible and secure solutions for both the management of the ever more broad, complexly-networked Internet of Things, and also for the support of various business models.

ACKNOWLEDGEMENT

We would like to thank our mentor Assistant Professor P.R.Sidda reddy for guidance and help throughout our project. We are also thank full to our institute S.V college of engineering, Tirupati,, for providing all the facilities needed for our project.

REFERENCES

[1]J. Granderson et al., “Small- and medium-sized commercial building monitoring and controls needs: A scoping study,” Pacific Northwest National Lab., Richland, WA, USA, Tech. Rep. PNNL-22169, Oct. 2012.
[2] C. Beckel, W. Kleiminger, T. Staake, and S. Santini, “Improving devicelevel electricity consumption breakdowns in private households using ON/OFF events,” ACM SIGBED Rev., vol. 9, pp. 32–38, 2012.
[3] A. Marchiori and Q. Han, “Using circuit-level power measurements in household energy management systems,” in Proc. 1st ACM Workshop BuildSys’09 Embedded Sensing Syst. Energy-Efficiency Buildings, New York, NY, USA, 2009, pp. 7–12.
[4] M. Figueiredo, A. de Almeida, and B. Ribeiro, “Home electrical signal disaggregation for non-intrusive load monitoring (NILM) systems,” Neurocomputing, vol. 96, pp. 66–73, Jan 11, 2012.
[5] C. Hsueh-Hsien, L. Ching-Lung, and Y. Hong-Tzer, “Load recognition for different loads with the same real power and reactive power in a nonintrusive load-monitoring system,” in Proc. 12th Int. Conf. Comput. Supported Cooperative Work Des. 2008 (CSCWD), pp. 1122–1127.

AUTHOR’S PROFILES:

G.Bhanu Prakash,
PG Scholar,
Department Of Electronics And
Communication Engineering(Embedded Systems),
S.V. College Of Engineering, Tirupati, A.P, India

P.R.Sidda Reddy,
Assistant Professor,
Department Of Electronics And
Communication Engineering,
S.V. College Of Engineering, Tirupati, A.P, India